PF	Product Fiche according to (EU) No 65/2014					
S	Supplier's name or trade mark Model identifier	V-ZUG AE6T6FTLG				
M						
	Annual Energy Consumption	AEC hood	31.2	kWh/a		
	Energy Efficiency Class	EEI class	A+			
	Fluid Dynamic Efficiency	FDE hood	34.7	%		
	Fluid Dynamic Efficiency class	FDE class	Α			
	Light Efficiency	LE hood	28.0	lux/W		
	Lighting Efficiency Class	LE class	Α			
	Grease Filtering Efficiency	GFE hood	82.0	%		
	Grease Filtering Efficiency class	GFE class	С			
	Minimum Air Flow in normal use	Q min	247	m³/h		
	Maximum Air Flow in normal use	Q max	452	m³/h		
	Air Flow at intensive/boost setting	Q boost	653	m³/h		
	A-weighted Sound Power Emission at minimum speed	SPE min	38	dB(A) re 1pW		
	A-weighted Sound Power Emission at maximum speed	SPE max	53	dB(A) re 1pW		
	A-weighted Sound Power Emission at intensive or boost speed	SPE boost	64	dB(A) re 1pW		
	Power consumption off mode	Po	0.00	W		
	Power consumption in standby mode	Ps	0.48	W		

Additional Information according to (EU) No 66/2014				
Time increase factor	f	0.8		
Energy Efficiency Index	EEI hood	42.0	%	
Measured air flow rate at best efficiency point	Q bep	380.6	m³/h	
Measured air pressure at best efficiency point	P bep	341	Pa	
Maximum air flow	Q max	657	m³/h	
Measured electric power input at best efficiency point	W bep	103.0	W	
Nominal power of the lighting system	WL	4	W	
Average illumination of the lighting system on the cooking surface	E middle	113	lux	

3011080001031 103340325VZ