

| PF | Product Fiche according to (EU) No 65/2014 | | | |
|-----------|---|-------------------|-------------|--------------|
| S | Supplier's name or trade mark | V-ZUG | | |
| M | Model identifier | AW6T9LQTLG | | |
| | Annual Energy Consumption | AEC hood | 28.2 | kWh/a |
| | Energy Efficiency Class | EEl class | A+ | |
| | Fluid Dynamic Efficiency | FDE hood | 36.3 | % |
| | Fluid Dynamic Efficiency class | FDE class | A | |
| | Light Efficiency | LE hood | 28.0 | lux/W |
| | Lighting Efficiency Class | LE class | A | |
| | Grease Filtering Efficiency | GFE hood | 89.5 | % |
| | Grease Filtering Efficiency class | GFE class | B | |
| | Minimum Air Flow in normal use | Q min | 247 | m³/h |
| | Maximum Air Flow in normal use | Q max | 452 | m³/h |
| | Air Flow at intensive/boost setting | Q boost | 675 | m³/h |
| | A-weighted Sound Power Emission at minimum speed | SPE min | 38 | dB(A) re 1pW |
| | A-weighted Sound Power Emission at maximum speed | SPE max | 52 | dB(A) re 1pW |
| | A-weighted Sound Power Emission at intensive or boost speed | SPE boost | 63 | dB(A) re 1pW |
| | Power consumption off mode | Po | 0.00 | W |
| | Power consumption in standby mode | Ps | 0.48 | W |

| Additional Information according to (EU) No 66/2014 | | | | |
|--|--|----------|--------------|------|
| | Time increase factor | f | 0.7 | |
| | Energy Efficiency Index | EEl hood | 38.9 | % |
| | Measured air flow rate at best efficiency point | Q bep | 371.7 | m³/h |
| | Measured air pressure at best efficiency point | P bep | 355 | Pa |
| | Maximum air flow | Q max | 675 | m³/h |
| | Measured electric power input at best efficiency point | W bep | 100.0 | W |
| | Nominal power of the lighting system | WL | 4 | W |
| | Average illumination of the lighting system on the cooking surface | E middle | 113 | lux |